



Hollows - Square

SECTION NUMBER	A	T	R1	R2	MASS kg/m	OUTSIDE PERIM	STOCKED IN ANODISED
9609	12.70	1.60			0.189	50.80	
30211~	16.00	1.20	1.60		0.187	61.25	
5728	19.00	1.60	2.40	0.80	0.301	76.00	
8950	20.00	1.50			0.300	80.00	
8777	20.00	3.00	3.00		0.530	74.85	
9675*	25.00	1.40	2.40	1.00	0.346	95.90	
6614	25.00	1.60			0.404	100.00	
N285	25.00	1.80	3.00		0.432	94.85	
9784	25.00	3.00			0.713	99.70	
8778+	25.00	3.00	3.00		0.695	94.85	
7841+	30.00	2.00	2.50	1.50	0.596	115.70	
6947	30.00	3.00			0.875	120.00	
K362	32.00	2.00			0.650	128.00	
J169	32.00	3.00			0.943	128.00	
G677+	33.90	1.45	2.50		0.498	131.31	
K911	40.00	1.60			0.666	160.00	
9193	40.00	1.60	3.00	1.40	0.647	154.85	
G097	40.00	2.00			0.824	160.00	
30196^	40.00	2.00	2.40		0.811	155.88	
X592**	40.00	3.00			1.203	160.00	
N737+	40.00	3.00	3.00	1.00	1.185	154.85	
32003	40.00	5.00	2.50		1.883	155.71	
1468	44.45	2.03			0.933	177.80	
J309	50.00	1.60			0.840	200.00	
K132	50.00	1.60	6.00	4.00	0.801	189.90	
33479+	50.00	2.00	3.00	1.00	1.022	194.85	
31350+	50.00	2.00	6.40	4.40	0.990	189.01	
9746	50.00	2.50			1.283	200.00	
5917+	50.00	3.00			1.523	200.00	
32565+	50.00	3.00	3.00		1.510	194.85	
32734^*	50.00	5.00	4.00	2.00	2.411	193.13	
X549	50.80	3.18	3.00		1.621	198.05	
Z912	60.00	1.40	1.00	0.30	0.887	238.28	
K308	65.00	2.50			1.694	260.00	
K323	75.00	3.00			2.341	300.00	
33133"	75.00	4.00	6.00		3.004	289.70	
33397~	76.20	3.00	6.00	3.00	2.318	294.50	
X550~	76.20	6.35	15.90	9.60	4.434	277.50	
Z320#	100.00	3.00			3.154	400.00	
36058	100.00	5.00	3.00	0.50	5.129	394.85	
17231^-	150.00	2.90	2.00		4.615	596.57	



+ Also available in 6.0m lengths

* Also available in 6060 T4

** Also available in 6061 T5 in 6m lengths

Also available in 4.0m and 6.0m lengths

^ Also available in 6.0m and 6.5m lengths

~ Available in 6.0m lengths only

" Available in 6061 T6 in 5.0m lengths only

- Available in 2.8m, 3.7m & 6.5m lengths only

^* Also available in 6005 T6

For NZ based customers. All lengths are stocked in 6060 T5 - mill finish - 5m lengths (unless specified)
All peripheries less than 100mm are deemed 100mm for surface finish purpose