



Unequal Angles

SECTION NUMBER	A	B	T	R	MASS kg/m	OUTSIDE PERIM	STOCKED IN ANODISED
5514	20.00	12.00	1.60		0.132	64.00	✓
5970	20.00	12.00	3.00		0.235	64.00	
9325	25.00	12.00	1.50		0.144	74.00	✓
5511	25.00	20.00	1.60		0.188	90.00	
J074	25.00	20.00	3.00		0.341	90.00	
5931	30.00	25.00	2.00		0.286	109.57	
0460	32.00	19.00	3.00		0.388	102.00	
9328	32.00	20.00	1.50		0.205	104.00	
5974	32.00	25.00	3.00		0.437	114.00	
6670	38.00	19.00	1.60		0.239	114.00	
7084	40.00	12.00	1.50		0.205	104.00	
9745	40.00	12.00	3.00		0.397	104.00	
9329	40.00	20.00	1.50		0.237	120.00	
8459	40.00	20.00	1.60		0.252	120.00	✓
6076	40.00	20.00	3.00		0.462	120.00	✓
5509	40.00	25.00	1.60		0.275	130.00	✓
8517	40.00	25.00	3.00		0.502	130.00	
J456	50.00	20.00	1.50		0.278	140.00	
31043	50.00	20.00	3.00		0.545	140.00	
5903	50.00	25.00	1.60		0.317	150.00	
5323	50.00	25.00	3.00		0.585	150.00	
9753	60.00	25.00	3.00		0.664	170.00	
6428	70.00	25.00	1.60		0.403	190.00	✓
Z965	70.00	40.00	1.60		0.470	220.00	
J105	70.00	40.00	2.00		0.585	220.00	
30193	75.00	25.00	3.00		0.789	200.00	
6788	75.00	50.00	3.00		0.988	250.00	
1658	76.20	50.80	4.75	6.86	1.601	251.06	
2386	76.20	50.80	6.35		2.085	254.00	
34033	80.00	40.00	3.00		0.951	240.00	
8266	100.00	25.00	3.00		0.992	250.00	
30641	100.00	50.00	3.00		1.195	300.00	
E927	100.00	50.00	6.00		2.341	300.00	
33919	150.00	75.00	6.00		3.561	450.00	



For NZ based customers. All lengths are stocked in 6060 T5 - mill finish - 5m lengths (unless specified)
All peripheries less than 100mm are deemed 100mm for surface finish purpose